



# AX-IT®



# Fast Acting No-Rinse Floor Stripper

This tried and proven formula quickly removes multiple layers of acrylic based floor finishes. Just apply and watch as the floor finish is quickly liquefied for easy removal by use of an auto scrubber or standard floor machine. This floor stripper leaves no alkaline residue requiring no flood rinsing and allows immediate application of floor finish. A neutralizer is not required after using this stripper. Reduce labor time with this effective and fast acting stripper as part of your overall floor care program to increase productivity.

# Uses

Use to remove sealers:

Acrylic

Use to remove finishes:

- Copolymer
- Metal crosslinked
- Styrene
- Thermoplastic
- Polymer

NOTE: This fast-acting stripper is a powerful product designed specifically for floor finish removal on resilient tile floors (vinyl and vinyl asbestos). It should not be used on wood floors or painted surfaces. Not recommended on linoleum or rubber tile floors since bleaching and softening may occur. Test first on asphalt tile in an inconspicuous area. Bleaching could occur.

# **Benefits**

- Powerful formula Cuts through layers of old finish in minutes.
  Low foaming makes pickup easy whether using a wet vacuum or an automatic scrubber.
- Rinse free This stripper never requires rinsing as no alkaline residue will be left on the floor. Detail mopping of slurry trails and edges is desirable.

### **Properties**

Clear, slight amber
None
Sassafras
3 cycles
None
13.5 - 14.0
12.5 - 13.0
1 year
1.002

# **Directions For Use**

Read the entire label before using this product.

Recommended for removing water-based acrylic and urethane fortified floor finishes from all types of resilient tile and hard surfaces. Pre-test in a small area, color bleeding or discoloration may occur on linoleum, rubber tile or asphalt tile. Not recommended for stripping linoleum or sheet vinyl floors.

Sweep or dust mop the floor to remove any large debris. Dilute with cool to warm water. For light to medium stripping, dilute 18 oz./gal. or 120 mL/L (1:7) of water. For heavy stripping, dilute 43 oz./gal. or 250 mL/L (1:3) of water. Apply solution liberally to floor surface. Allow 4 - 5 minutes contact time. Be sure to keep surface wet at all times. Agitate with a low-speed rotary machine, automatic scrubber or stripping machine. Pick up the solution with a wet vacuum, an automatic scrubber or a mop and bucket and thoroughly rinse the floor. Allow floor to dry completely before applying finish or sealer. No flood rinsing is necessary if surface appears free of dust and residue.

# Safety

Keep out of reach of children. For institutional and commercial use. CORROSIVE. Causes burns. Vapors harmful. Harmful if swallowed. Contains Potassium Hydroxide, 2-Butoxyethanol and Monoethanolamine. Avoid contact with skin and eyes. Wear chemical anti-splash goggles and suitable gloves and boots. FIRST AID: Remove contaminated clothing immediately. SKIN AND EYES: Flush skin and eyes immediately with large quantities of water for at least 15 minutes. Seek immediate medical attention. INGESTION: If swallowed, contact a poison control center immediately for treatment advice. Have conscious person take sips of water if able to swallow. Never give anything by mouth to an unconscious person. Do not induce vomiting unless instructed to do so by poison control center or doctor. INHALATION: Remove to fresh air. If not breathing, call 911 or ambulance, then administer artificial respiration, preferably mouth-to-mouth. SEE MATERIAL SAFETY DATA SHEET.

# Available In

Pail/5 Gallon (18.9 L): #15105-00 Drum/55 Gallon (208 L) #15155-00

Literature Item #15192-92

C1020 - Floor Care - Strippers

06.05

