

FLOOR SEALER



Metal Interlocked Acrylic Polymer Floor Sealer

This acrylic sealer is designed as a basecoat to protect floors for years. Hard, durable and detergent resistant, this sealer can be used on all types of resilient tile and terrazzo floors. It is also compatible with all water-based finishes. This high gloss sealer will not yellow or powder. This sealer is perfect for providing worn and damaged floor tiles a smooth surface for floor finish application.



Uses

- Factories
- Hospitals
- Offices
- Schools
- Showrooms
- Supermarkets
- Warehouses

Benefits

- Durability Acrylic polymer provides long lasting protection.
- Easy to apply Won't yellow or powder.
- Compatible with all water-based finishes or waxes.
- Versatile Can be used on terrazzo and resilient tile.
- High gloss enhances the appearance of the finish.

Properties

| Color | Milky white |
|--------------------|----------------------------|
| Color (dried film) | Clear |
| Coverage | 1500 - 2000 sq. ft./gallon |
| Flash point | None |
| Fragrance | |
| Leveling | Excellent |
| Solids | >18% |
| pH | 8.1 - 8.9 |
| Shelf life | 1 year |
| Specific gravity | 1.02 |
| | |

Directions For Use

Read the entire label before using this product.

RESTORATIVE MAINTENANCE: Completely remove all old wax, finish and soil from the floor surface following strip procedure instructions on stripper label. Floor surface must be clean, dry and free of residue before sealer is applied. Rinse with water if necessary. Apply sealer in uniform, thin to medium coats using a clean synthetic finish mop or applicator system. Allow each coat to dry thoroughly before applying additional coats, usually 20 - 30 minutes. Two coats of sealer are recommended. This sealer can be used as a finish coat, however, for a better shine, increased protection and easier maintenance, we recommend the application of 2 - 4 coats of a floor finish that best fits your maintenance program. NOTE: Slip resistance meets or exceeds (ASTM D 2047-93) James Machine 0.5 minimum.

Safety

Keep out of reach of children. For institutional and commercial use. **CAUTION:** Undiluted product may cause eye irritation. Avoid contact with eyes. Harmful if swallowed **FIRST AID:** SKIN: Flush with water. Seek medical attention if irritation persists. EYES: Flush with large quantities of water. Seek medical attention if irritation persists. INGESTION: Dilute with two glasses of water. Seek medical attention if symptoms persist.

Available In

Case/4 - 1 Gallon (3.78 L): Item #60704-00 Pail/5 Gallon (18.9 L): Item #60705-00 Drum/55 Gallon (208 L): Item #60755-00

Literature Item #60792-92

C1030 - Floor Care - Sealers

07.06

