



UNTOUCHABLE®



Metal Interlocked Floor Finish and Basecoat

This optically energized floor finish and base coat is for those who want the highest gloss and wear with the least amount of labor. This metal cross-linked, polymer finish gives your floor a depth of gloss like you've never seen before. One coat does the job of two coats of an ordinary finish. This finish is detergent resistant, nonscuffing, durable and maintains its high gloss without burnishing – a real labor saver. It's suitable for use on all floors and may be maintained by damp mopping. Excellent leveling makes it easy to apply. This product makes a great basecoat, providing a smooth glossy foundation for all other floor finishes.

Uses

- Resilient flooring
- Terrazzo

Features

- Can be used through Betco QUICKCOAT® II Applicator for enhanced productivity.
- Durability – This metal cross-linked, acrylic polymer formula provides extended wear and superior protection for your floor covering.
- Appearance – The high gloss resists black heel marks and detergent. It never yellows, giving you a cleaner, brighter looking floor.
- Ease – Self-leveling, excellent flow for easy application with little or no mop drag. Self sealing for reduced cost.
- Versatile – For use on all resilient flooring as well as terrazzo. May be used as a basecoat for other floor finishes.

Properties

Coverage.....	2,000 - 3,000 sq. ft./gal.
Drying time	30 - 40 minutes
Fragrance	Mild
Freeze/thaw stability	3 cycles
Gloss (ASTM D 1455-87)	One coat 80 - 85 Two coats 97 - 98
Heel mark resistance	Very good
Leveling	Excellent
pH	8.1 - 8.9
Powdering resistance	Excellent
Recoat	Very good
Specific gravity	1.03
Free styrene content.....	0.0
Shelf life.....	1 year

Utilizes Betco's XBF technology for added brightness and extended durability.

KEEP FROM FREEZING

Authorized Betco Distributor



Directions For Use

Read the entire label before using this product.

Recommended for use on all types of resilient tile flooring and properly prepared hard surfaces. RESTORATIVE MAINTENANCE: Completely remove all old wax, finish and soil from floor surface following strip procedure instructions on stripper label. Floor surface must be clean, dry and free of residue before finish is applied. Rinse with clean water if necessary. Apply finish in uniform, thin to medium coats using a clean synthetic finish mop or applicator system. Allow each coat to dry thoroughly before applying additional coats, usually 20 - 30 minutes. Elevated temperatures and humidity may extend dry time. 4 - 5 coats of finish are recommended. **Note: This product is a self sealing finish, however, if tile is old, worn or porous, initially applying 1 - 2 coats of a sealer will enhance gloss and long term performance.** ROUTINE MAINTENANCE: Sweep large debris and dust mop (using a water based treatment). Damp mop or automatic scrub using a neutral pH cleaner. Buff or burnish the floor as desired. The use of a cleaner/restorer is recommended to condition the floor and extend the time between top scrub and recoating. INTERIM MAINTENANCE: Sweep large debris and dust mop (using a water-based treatment). Top scrub the floor using a top scrub cleaner and recommended floor pad to remove the top soiled layers of finish. Floor surface must be clean, dry and free of residue before finish is applied. Apply 1 - 2 coats of finish as directed above. **Note: Slip resistance meets or exceeds standard, (ASTM D 2047-04) James Machine 0.5 minimum.**

Safety

Keep out of reach of children. For institutional and commercial use. **WARNING: MAY CAUSE EYE IRRITATION.** Contains glycol ether. Avoid contact with skin and eyes. Harmful if swallowed. **FIRST AID:** If splashed on skin or in eyes, flush with large quantities of water. Seek medical attention if irritation persists. If swallowed, drink two glasses of water. Call a physician.

Available In

- Case/4 - 1 Gallon (3.78 L): Item #60604-00
- Box/2-1.125 Gallon Bags (4.25 L): Item #60659-00 (QUICKCOAT® II)
- BIB/5 Gallons (18.9 L): Item #60639-00
- Pail/5 Gallon (18.9 L): Item #60605-00
- Drum/55 Gallon (208 L): Item #60655-00

Literature Item #60692-92

C1010 - Floor Care - Finishes - Resilient

08.09

