



Buckeye[®]

LUCENT[™]

Urethane Fortified Floor Finish

- **Urethane fortified acrylic system**
- **Designed for resilient and non-resilient floors**
- **U.L. listed for slip resistance**
- **Clear, non-yellowing**
- **Burnishable and non-powdering**
- **Durable - reduces strip outs**
- **Oustanding leveling**
- **Easy application**
- **Excellent depth of gloss**
- **Black mark resistant**
- **Scratch resistance**



Buckeye **Lucent**[™] is a water-based urethane fortified floor finish, designed to beautify and protect resilient and non-resilient floors providing a high gloss, durable, burnishable, slip resistant surface.

DIRECTIONS FOR USE:

1. Strip floor using Buckeye Revelation[®], Juggernaut[®] or RipSaw[™] following label directions.
2. After picking up solution rinse floor.
3. Allow floor to fully dry before applying **Lucent**.

APPLICATION:

1. Use a clean mop and bucket or applicator.
2. Saturate mop and press firmly into wringer to remove excess **Lucent**. Do not wring mop.
3. Apply **Lucent** using an overlapping figure-eight motion.
4. Allow to dry (usually 30 to 40 minutes). Temperature, humidity and air movement affect dry time.
5. Apply additional coats until desired gloss is achieved. Apply no more than four (4) coats in a 24-hour period.
6. Allow **Lucent** to properly cure for 48 hours before scrubbing.

MAINTENANCE:

1. Dust mop floor.
2. Damp mop or autoscrub floor, as needed, using Buckeye Crossbow[®], Straight-Up[®], Green Light[™] or Buckeye Blue following label directions.
3. Top scrub and recoat, as needed.

Available in:



TECHNICAL SPECIFICATIONS

pH	8.0 ± 0.2
Weight/Gallon	8.58 lbs
Freeze-Thaw Stability	Passes 3 Cycles
Removability	Excellent
Slip Resistance	U.L. Classified



Buckeye International, Inc.

2700 Wagner Place • Maryland Heights • Missouri 63043 • 800.321.2583
www.buckeyeinternational.com